

E-HEAT GUTTER flxheat

For frost protection, ice, and snowmelting

Technical data

Voltage	230 V
Min. bend radius	35 mm
Max. temp	85 °C
Min. temp	-30 °C
Nom. dimension	10.5 x 5.9 mm
Approvals	CE
Warranty	3 years
Length tolerance	+/- 2 %



Item	Type	Description	Effect/10°C	Power	Max length m/+10 °C	Max length m/0 °C	Max length m/-20 °C
40040023	SeG23	Heat-Self Gutter 23 W@+10C black	23 W	16 A	-	44	33
			23 W	20 A	-	53	41
			23 W	30 A	-	58	45
			40 W/m@0C		-		

Description

Self-regulating heating cable 23 W

A self-regulating heating cable with earthing screen of aluminium foil, which makes it very easy for the electrician to terminate it in relation to the tin-plated copper braid. The cable is mostly used for outdoor frost protection for gutters, drainpipes, and roofs.

The cable's nominal dimension is 10.5 x 5.9 mm and the outer sheath is of the type TPE and also UV resistant.

The maximum temperature of the cable is 85 °C/65 °C and the minimum installation temperature is -30 °C.

The cable provide its full power of 40 W/m at 0 °C in ice water. Properly installed, the E-Heat Gutter will prevent unpleasant moisture damage to roofs, frost damage and building of icicles.