

FLXBOARD

Underlay for AluMat, 3 and 6 mm

Technical data

Flxboard 3 mm

Material	Extruded Polystyrene / XPS
Dimensions (H,W,L)	3 x 500 x 1200 mm
Weight	150 g/m ²
Density (EN ISO 845)	40 kg/m ³
Moisture protection (vol. %)	0,08 %
Load	9 t/m ²
U-value	9,26 W/m ² K
Max. temperature	80° C
Sound reduction	22 dB
Warranty	10 years
Standard	CE

Flxboard 6 mm

Material	Extruded polystyren / XPS
Dimensions (H, W, L)	6 x 500 x 1200 mm
Weight	200 g/m ²
Density (EN ISO 845)	32 kg/m ³
Moisture protection (vol.%)	0,06 %
Load	9 t/m ²
U-value	4,64 W/m ² K
Max. temperature	80° C
Sound reduction	22 dB
Warranty	10 years
Standard	CE

Item	Type	Description	Height	Width	Length
40101030	RF3	Flxboard 3 (sold in 6 m ² packages only)	3 mm	500 mm	1200 mm
40101060	RF6	Flxboard 6 (sold in 6 m ² packages only)	6 mm	500 mm	1200 mm

Description

Flxboard is a 3 or 6 mm thin sheet of insulating material of extruded polystyrene.

Flxboard is used as underlay for AluMat for wood, parquet and laminate flooring. The Flxboard reduces sounds and take up to 2.2 mm unevenness on the subfloor surface.

Flxboard is sold only in packages of 6 m².

Important!

Do not install together with PA, ie. nylon, as these materials reacts chemically.

