

Heat-Self TTR

Self-Limiting Heating Cable

Max. 85°C

For industrial use.
For frost protection and temperature
maintenance of pipes.

Thermoplast or fluoropolymer outer coating.



Technical Data

Voltage	230 V ~ 50 Hz
Cable diameter	11.5 x 5.5 mm
Inside of cable protected against moist	Yes
Authorisation	CE, EX-KEMA
Cable type	Self-limiting heating cable
Ground shield	Tinned copper
Outer sheath	Thermoplast (-BO) or Fluoropolymere (-BOT)
Max. temp. on cable	65 °C / 85 °C
Min. bending radius	25 mm
Warranty	3 years
Maks. cable length (depending on size)	45 m - 205 m
Min. installation temperature	-30 °C
Length tolerance	+/- 2 %

Heat-Self TTR

Item	Type	Description	Power	Max temperature	
				On	Off
	10TTR-2-BO	Self-lim. Heating Cable TTR 10 W/m Thermoplast	10 W/m@10 °C	65 °C	85 °C
	10TTR-2-BOT	Self-lim. Heating Cable TTR 10 W/m Flourpolym.	10 W/m@10 °C	65 °C	85 °C
	15TTR-2-BO	Self-lim. Heating Cable TTR 15 W/m Thermoplast	15 W/m@10 °C	65 °C	85 °C
	15TTR-2-BOT	Self-lim. Heating Cable TTR 15 W/m Flourpolym.	15 W/m@10 °C	65 °C	85 °C
	20TTR-2-BO	Self-lim. Heating Cable TTR 20 W/m Thermoplast	20 W/m@10 °C	65 °C	85 °C
	20TTR-2-BOT	Self-lim. Heating Cable TTR 20 W/m Flourpolym.	20 W/m@10 °C	65 °C	85 °C
	25TTR-2-BO	Self-lim. Heating Cable TTR 25 W/m Thermoplast	25 W/m@10 °C	65 °C	85 °C
	25TTR-2-BOT	Self-lim. Heating Cable TTR 25 W/m Flourpolym.	25 W/m@10 °C	65 °C	85 °C
40042033	33TTR-2-BO	Self-lim. Heating Cable TTR 33 W/m Thermoplast	33 W/m@10 °C	65 °C	85 °C
	33TTR-2-BOT	Self-lim. Heating Cable TTR 33 W/m Flourpolym.	33 W/m@10 °C	65 °C	85 °C