



MOBILE HEATING WRAP WITH VELCRO CLOSURE

Frost protection for pipes and drains

Frost protection especially for pipes and drains at construction sites. The structure of the product is a self-limiting heating cable with an earthing screen of aluminum foil – effect 15 W/m at 10°C – which is mounted in an insulated foil that can be wrapped around the pipe and closed with velcro.

The heating wrap can be used on pipes up to 50 mm. For larger elements and pipe dimensions, two or more wraps can be used, which are simply held together using same Velcro.

This Product provides a quickly and efficiently mounting at the construction site that is easy to dismantle and can be re-used. The heating wrap can be delivered with a DK, Schuko or three-poled IEC 309 plug. The minimum installation temperature is -30°C. Its use includes temporary installations for on-site office trailers, mobile bathrooms, and similar facilities.

Product range from 5 m - 25 m and comes in 5 sizes.

*** Must be controlled by thermostat**

ADVANTAGES:

- Very simple and fast installation with high efficiency
- Effective frost protection with built-in insulation
- Optimal Mobility
- The reusable design ensures repeated use and a long lifespan
- Avoid construction downtime
- Can be combined with one or more heating wraps for larger pipe dimensions
- Plug-and-Play
- 3-year warranty

TECHNICAL DATA

Voltage	230 V ~ 50 Hz
Supply Cable	1.5 m
Ingress Protection	IP44
Effect	15 W/m
Material	PE-foil 0.15 mm + insulation
Recommended fuse	10 A
Approval	CE
Warranty	3 Years



APPLICATIONS

Water and drain-pipes



ACCESSORIES

Thermostat

LINK TO OUR WEBSITE





PRODUCT OVERVIEW



MOBILE HEATING WRAP – Schuko plug

DESCRIPTION	PLUG	EFFECT WATT/10 °C	POWER
Heating Wrap - 5 m	Schuko	85 W	0.4 A
Heating Wrap - 10 m	Schuko	170 W	0.7 A
Heating Wrap - 15 m	Schuko	255 W	1.1 A
Heating Wrap - 20 m	Schuko	340 W	1.6 A
Heating Wrap - 25 m	Schuko	425 W	1.8 A

MOBILE HEATING WRAP – IEC309 Plug

DESCRIPTION	PLUG	EFFECT WATT/10 °C	POWER
Heating Wrap - 5 m	IEC309	85 W	0.4 A
Heating Wrap - 10 m	IEC309	170 W	0.7 A
Heating Wrap - 15 m	IEC309	255 W	1.1 A
Heating Wrap - 20 m	IEC309	340 W	1.6 A
Heating Wrap - 25 m	IEC309	425 W	1.8 A

MOBILE HEATING WRAP – DK plug

DESCRIPTION	PLUG	EFFECT WATT/10 °C	POWER
Heating Wrap - 5 m	DK	85 W	0.4 A
Heating Wrap - 10 m	DK	170 W	0.7 A
Heating Wrap - 15 m	DK	255 W	1.1 A
Heating Wrap - 20 m	DK	340 W	1.6 A
Heating Wrap - 25 m	DK	425 W	1.8 A

Heatcom Corporation A/S
Barmstedt Allé 6
DK-5500 Middelfart
Tel. +45 63 41 77 77
Sales@Heatcom.dk