

PIPEGUARD

13 W/m



Technical data

| | |
|-------------------------|------------------------------|
| Voltage | 230 V ~ 50 Hz |
| Cable diameter | Ø7 mm |
| Insulation inner sheath | Teflon, FEP |
| Authorisation | CE |
| Cable buildup | 2 conductors + ground shield |
| Ground shield | Tinned copper |
| Outer sheath | PVC |
| Max. temp. on cable | 90 °C |
| Warranty | 3 years |
| Resistance tolerance | - 5 % / +10 % |



DK plug



| Item | Type | Description | Power | Current | Resistance |
|----------|----------------|-------------------------------------|-------|---------|------------|
| 50430014 | FlxF70E013-014 | PipeGuard 1.4 m 13 W/m Schuko Plug | 19 W | 0.1 A | 2800 Ω |
| 50430020 | FlxF70E013-020 | PipeGuard 2.0 m 13 W/m Schuko Plug | 26 W | 0.1 A | 2000 Ω |
| 50430030 | FlxF70E013-030 | PipeGuard 3.0 m 13 W/m Schuko Plug | 39 W | 0.2 A | 1350 Ω |
| 50430040 | FlxF70E013-040 | PipeGuard 4.0 m 13 W/m Schuko Plug | 53 W | 0.2 A | 1000 Ω |
| 50430050 | FlxF70E013-050 | PipeGuard 5.0 m 13 W/m Schuko Plug | 66 W | 0.3 A | 800 Ω |
| 50430080 | FlxF70E013-080 | PipeGuard 8.0 m 13 W/m Schuko Plug | 107 W | 0.5 A | 496 Ω |
| 50430105 | FlxF70E013-105 | PipeGuard 10.5 m 13 W/m Schuko Plug | 140 W | 0.6 A | 378 Ω |
| 50430140 | FlxF70E013-140 | PipeGuard 14.0 m 13 W/m Schuko Plug | 185 W | 0.8 A | 286 Ω |
| 50430185 | FlxF70E013-185 | PipeGuard 18.5 m 13 W/m Schuko Plug | 247 W | 1.1 A | 215 Ω |
| 50430225 | FlxF70E013-225 | PipeGuard 22.5 m 13 W/m Schuko Plug | 300 W | 1.3 A | 176 Ω |
| 50430380 | FlxF70E013-380 | PipeGuard 38.0 m 13 W/m Schuko Plug | 475 W | 2.1 A | 111 Ω |
| 50430450 | FlxF70E013-450 | PipeGuard 45.0 m 13 W/m Schuko Plug | 475 W | 2.5 A | 92 Ω |

Description

Frost Protection of Pipes

Pipeguard with built-in thermostat and mounted plug protects water pipes against frost.

Pipeguard is mounted on the pipes, which is insulated subsequently. The built-in thermostat controls the temperature, so it can be kept above zero.

When the temperature is high enough, Pipeguard is switched off. Pipeguard is switched on when the cold arrives. Can also be used on plastic tubes, mounted with aluminum tape. Aluminum Tape does not accompany the product.

Pipeguard comes in different lengths from 1.4 m to 45 m.
Mounted Schuko plug.