

Technical data

Voltage	230 V ~ 50 Hz
Cable diameter	7.9 x 5.6 mm
Inside of cable protected against moist	Yes
Authorisation	CE, Semko
Cable type	Self-limiting heating cable
Ground shield	Tinned copper
Outer sheath	Thermoplast (-BO) or Fluoropolymere (-BOT)
Max. temp. on cable	65 °C / 85 °C
Min. bending radius	25 mm
Warranty	3 years
Maks. cable length (depending on size)	41 m - 100 m
Min. installation temperature	-30 °C
Length tolerance	+/- 2 %



Item	Type	Description	Power	Max temperature	
				On	Off
40040011	11TTM-2-BO	Self-lim. Heating Cable TTM 11 W/m Thermoplast	11 W/m@5 °C	65 °C	65 °C
40040911	11TTM-2-BOT	Self-lim. Heating Cable TTM 11 W/m Flourpolym.	11 W/m@5 °C	65 °C	65 °C
40040017	17TTM-2-BO	Self-lim. Heating Cable TTM 17 W/m Thermoplast	17 W/m@5 °C	65 °C	65 °C
40040917	17TTM-2-BOT	Self-lim. Heating Cable TTM 17 W/m Flourpolym.	17 W/m@5 °C	65 °C	65 °C
40040020	20TTM-2-BO	Self-lim. Heating Cable TTM 20 W/m Thermoplast	20 W/m@5 °C	65 °C	65 °C
40040920	20TTM-2-BOT	Self-lim. Heating Cable TTM 20 W/m Flourpolym.	20 W/m@5 °C	65 °C	65 °C

Description

Self-Limiting Heating Cable

Max. 65°C

For installations on locations with light mechanical influence.

For frost protection and temperature maintenance of pipes.

Thermoplast or flourpolymer outer coating.