

# TTR

## Self-limiting cable



## Technical data

Voltage	230 V ~ 50 Hz
Cable diameter	11.5 x 5.5 mm
Inside of cable protected against moist	Yes
Authorisation	CE, EX-KEMA
Cable type	Self-limiting heating cable
Ground shield	Tinned copper
Outer sheath	Thermoplast (-BO) or Fluoropolymere (-BOT)
Max. temp. on cable	65 °C / 85 °C
Min. bending radius	25 mm
Warranty	3 years
Maks. cable length (depending on size)	45 m - 205 m
Min. installation temperature	-30 °C
Length tolerance	+/- 2 %



Item	Type	Description	Power	Max temperature	
				On	Off
40060010	10TTR-2-BO	Self-lim. Heating Cable TTR 10 W/m Thermoplast	10 W/m@10 °C	65 °C	85 °C
40060910	10TTR-2-BOT	Self-lim. Heating Cable TTR 10 W/m Flourpolym.	10 W/m@10 °C	65 °C	85 °C
40060015	15TTR-2-BO	Self-lim. Heating Cable TTR 15 W/m Thermoplast	15 W/m@10 °C	65 °C	85 °C
40060915	15TTR-2-BOT	Self-lim. Heating Cable TTR 15 W/m Flourpolym.	15 W/m@10 °C	65 °C	85 °C
40060020	20TTR-2-BO	Self-lim. Heating Cable TTR 20 W/m Thermoplast	20 W/m@10 °C	65 °C	85 °C
40060920	20TTR-2-BOT	Self-lim. Heating Cable TTR 20 W/m Flourpolym.	20 W/m@10 °C	65 °C	85 °C
40060025	25TTR-2-BO	Self-lim. Heating Cable TTR 25 W/m Thermoplast	25 W/m@10 °C	65 °C	85 °C
40060925	25TTR-2-BOT	Self-lim. Heating Cable TTR 25 W/m Flourpolym.	25 W/m@10 °C	65 °C	85 °C
40060033	33TTR-2-BO	Self-lim. Heating Cable TTR 33 W/m Thermoplast	33 W/m@10 °C	65 °C	85 °C
40060933	33TTR-2-BOT	Self-lim. Heating Cable TTR 33 W/m Flourpolym.	33 W/m@10 °C	65 °C	85 °C

## Description

### Self-Limiting Heating Cable

Max. 85°C

For industrial use.  
For frost protection and temperature maintenance of pipes.

Thermoplast or flourpolymer outer coating.