



UNDERLAY FOR ALUMAT

Reflector 3 mm, 6 mm

Reflector plates are thin sheets of insulating material of medium-hard extruded polystyrene, used as underlay for AluMat Underfloor Heating (for wooden and laminate flooring). Reflector plates provide thermal and sound insulation and smooth out unevenness of the subfloor surface.

Underlay is available in 3 and 6-mm thickness and comes in 6 m² packages.



TECHNICAL DATA

| | REFLECTOR 3 | REFLECTOR 6 |
|------------------------------|----------------------------|----------------------------|
| Material | Extruded Polystyrene / XPS | Extruded Polystyrene / XPS |
| Dimensions (H,W,L) | 3 x 500 x 1200 mm | 6 x 500 x 1200 mm |
| Weight | 150 g/m ² | 200 g/m ² |
| Density (EN ISO 845) | 40 kg/m ³ | 32 kg/m ³ |
| Moisture protection (vol. %) | 0,08 % | 0,06 % |
| Load | 9 t/m ² | 9 t/m ² |
| U-value | 9,26 W/m ² K | 4,64 W/m ² K |
| Max. temperature | 80° C | 80° C |
| Sound reduction | 22 dB | 22 dB |
| Warranty | 10 years | 10 years |
| Standard | CE | CE |

LINK TO OUR WEBSITE



Version 1-022021

Heatcom Corporation A/S
Korsholm Allé 14
DK-5500 Middelfart
Tel. +45 63 41 77 77
Sales@Heatcom.dk