



ALUMAT 80, 140 W/m²



Alumat is a unique heating mat, specially developed to be used on an existing stable floor directly beneath wooden and laminate flooring – without requiring covering by levelling compounds. No more wet trade – dry and clean installation make the heating mat impressively easy to work with. All that is needed is a hobby-knife and scissors! The ultra-thin design of the mat adds minimal build height to your floor construction.

AluMat must be fitted on a layer of insulating underlay, suitable for the electric underfloor heating. For these purposes, we recommend using Reflector 3, Reflector 6 or another underlay with similar properties. Heatcom's Reflector plates smooth out unevenness of the subfloor surface, provide additional thermal and sound insulation and protect the heating mats against weight load, prolonging the lifetime of your floor.

We recommend using a thermostat with a floor sensor and temperature limiter at max. 27°C to avoid the risk of floor damage by too rapid heating and high temperature. With additional accessories, AluMat can be fitted beneath carpets, vinyl, linoleum, etc. Select a suitable manual or programmable thermostat from a wide range of Heatcom's Heat Controls.



ADVANTAGES:

- Dry and clean installation – no embedding required
- Ideal for use beneath wooden floors, parquet, laminate
- Ultra-thin design – adds minimal build height to floor construction
- Easy-to-install, simple cut and turn design
- Highly reliable and resistant to high temperatures
- Available in a wide range of sizes
- Danish Design
- Covered by a 15-year warranty



Version 1-052021

Heatcom Corporation A/S
Korsholm Allé 14
DK-5500 Middelfart
Tel. +45 63 41 77 77
Sales@Heatcom.dk