



GUTTER HEAT

Snow and ice melting on roofs and in gutters

Gutter Heat is designed for frost protection of gutters and downpipes but can also be used on the roof. If the heating cable is installed in a downpipe, it is typically fixed to a chain, hanging from a strain relief at the top of the downpipe.

Gutter Heat is a self-regulating heating cable with an output of 25 W/m, supplied complete with a factory-fitted plug and ready for on-site installation. The cable is equipped with a 2-meter neoprene connection cable and a molded plug.

The built-in thermostat ensures that the product is activated when the temperature drops below 3°C and switches off again when the temperature rises above 13°C.



TECHNICAL DATA

Nominal power	25 W/m @ 10 °C
Supply voltage	230 V
Cable dimension (BxH)	10,5 mm x 5 mm (+/-0,5 mm)
Conductor insulation	Polyolefine
Bus conductor	2 x 1,0 mm ²
Earthing	Aluminium mylar foil and copper conductor
Cable outer sheath	Polyolefine, UV stable
Colour	Black, RAL 9005
Thermostat	Bi-metal, ON 3 °C / OFF 13 °C
Supply cable	H05RN-F, 2 m
Permissible cable temperature	Max. 65 °C (85 °C unpowered)
Min. bending radius	30 mm, across surface (B)
Warranty	5 years
Min. installation temperature	-15 °C
Standards	IEC/EN 62395
Tolerance effect @ 10 °C	-10 %...+20 %

APPLICATIONS

Gutters, down pipes	✓
Roofs	✓

ACCESSORIES

Thermostat
Cable clips for gutters
Spacer clips
Chain
Crossbar
Edge protector

Version 3-012025

Heatcom Corporation A/S
Barmstedt Allé 6
DK-5500 Middelfart
Tel. +45 63 41 77 77
Sales@Heatcom.dk



PRODUCT OVERVIEW



GUTTER HEAT

DESCRIPTION	EFFECT	CURRENT	POWER/m @10° c
Gutter Heat 2,5 m, Schuko	60 W	0,3 A	25 W/m
Gutter Heat 6,0 m, Schuko	150 W	0,7 A	25 W/m
Gutter Heat 10,0 m, Schuko	250 W	1,1 A	25 W/m
Gutter Heat 12,0 m, Schuko	300 W	1,3 A	25 W/m
Gutter Heat 15,0 m, Schuko	375 W	1,6 A	25 W/m
Gutter Heat 20,0 m, Schuko	500 W	2,2 A	25 W/m
Gutter Heat 25,0 m, Schuko	625 W	2,7 A	25 W/m
Gutter Heat 30,0 m, Schuko	750 W	3,3 A	25 W/m
Gutter Heat 40,0 m, Schuko*	1000 W	4,3 A	25 W/m
Gutter Heat 50,0 m, Schuko*	1250 W	5,4 A	25 W/m

*Supply through separate thermostat

Heatcom Corporation A/S
Barmstedt Allé 6
DK-5500 Middelfart
Tel. +45 63 41 77 77
Sales@Heatcom.dk