



ACCESSORIES

Industrial applications

SELF-END • End termination for self-limiting cables.

Item no. 40059004

60x51x22mm • IP66 • Max. 40A • 72g • 1 pc/pack

Ex eb IIC T6...T3 Gb • Ex tb IIIC T85°C... 200°C Db (ATEX)



PT100 EX • 3-wire temperature sensor for industry, robust design with stainless steel probe tube (length 165mm). Incl. M20 cable gland.

Item no. 40059010

260x180x75mm • -50 to 450°C • AISI 316L sensor • 550g • 1 pc/pack



SELF-TEE • T-piece for self-limiting cables.

Item no. 40059005

126x68x22mm • IP66 • Max. 40A • 292g • 1 pc/pack

Ex eb IIC T6...T3 Gb • Ex tb IIIC T85°C... 200°C Db (ATEX)



SELF-BOX • Junction box for self-limiting cables • Incl. 2 pcs M25 cable glands and M25 plug.

Item no. 40059002

122x122x67mm • IP66 • Polyester • 1094g • 1 pc/pack

Ex eb IIC T6...T3 Gb • Ex tb IIIC T85°C... 200°C Db (ATEX)



CONNECTION KIT • Kit for use together with junction boxes.

Item no. 40059001

135x200x10mm • Silicone • 30g • 1 set/pack

Ex eb IIC T6...T3 Gb • Ex tb IIIC T85°C... 200°C Db (ATEX)



Version 2-082026

Heatcom Corporation A/S
Barmstedt Allé 6
5500 Middelfart
Tel. +45 63 41 77 77
Sales@Heatcom.dk



DATA SHEET



SELF-LIGHT • End termination for self-limiting cables, illuminated when the cable is active.

Heating cable entry through the base • incl. accessories for connection.

Item no. 40059006

210x85x90mm • IP66 • Max. 40 A • 240 Vac • 482g • 1 pc/pack



SELF-BOX-3 • Junction box for self-limiting cables • Incl. 1 pc M25 cable gland and M25 plug • Entry for 3 heating cables in the base

Item no. 40059007

160x160x90mm • IP66 • Polyester • Max. 40 A • 1860g • 1 pc/pack



BJW86 THERMOSTAT • Simple thermostat for installation directly on pipes • Connection via 2 pcs G3/4" cable glands (not included)

Item no. 40059008

Setpoint 0 - 120 °C

200x140x75mm • IP65 • Max. 25 A • 240 Vac • 1370g • 1 pc/pack



PTDC THERMOSTAT • Advanced thermostat for installation on wall or pipe • Connection via 2 pcs M25 cable glands plus M16 • Stainless steel mounting bracket included • ModBus RTU interface and alarm output

Item no. 40059009

Setpoint -60 - 200 °C

160x185x90mm • IP66 • Max. 32 A • 240 Vac • 4064g • 1 pc/pack

Ex eb ib mb IIC T4 Gb...T3 Gb • Ex tb IIIC T135°C Db (IECex)



LINK TO WEB



Heatcom Corporation A/S
Barmstedt Allé 6
5500 Middelfart
Tel. +45 63 41 77 77
Sales@Heatcom.dk