DATA SHEET

2 WARRANTY

# MOBILE HEATING WRAP

## Frost protection of water pipes and drains

The mobile heating wrap consists of self-limiting heating cable with an output of 15 W/m installed in an insulating wrap, which can be closed around pipes and the like by means of velcro closures.

The heating wrap can be used on pipes of up to Ø50 mm – for larger dimensions, 2 or more wraps can be used, which are simply chained together with the velcro closures.

This design allows lightning-fast and efficient installation and removal on the construction site, which makes the heating wrap suitable even for jobs of short duration.

The heating wrap can be supplied with DK, Schuko or IEC309 plug.

Minimum installation temperature is -30 °C.

Used among other things in temporary installations for site huts, mobile bathroom trailers and the like.

5 different lengths from 5 m up to 25 m.

The heating wrap requires a thermostat when the daytime temperature exceeds 5 °C. A suitable thermostat can be ordered as an accessory.



CE

### APPLICATIONS

| | |
|---|---|
| Outside of pipe | ✓ |
| Inside of pipe | |

### TECHNICAL DATA

| | |
|---|---|
| Supply voltage | 230 V - 50 Hz |
| Supply cable | H05RN-F, 2 m |
| Ingress protection | IP44 |
| Nominal power | 15 W/m @10 °C |
| Material | PE foil, grey/silver |
| Outer sheath | Polyolefin, special |
| Heating wrap width | 230 mm |
| Max. permissible cable temperature | 60 °C |
| Min. bending radius | 50 mm |
| Warranty | 2 years |
| Approval | CE |

### ACCESSORIES

| |
|---|
| Termination kit |
| Thermostat |

### LINK TO OUR WEBSITE

Version 2-102023

Heatcom Corporation A/S
Barmstedt Allé 6
5500 Middelfart
Tel. +45 63 41 77 77
Sales@Heatcom.dk

# PRODUCT OVERVIEW

2 WARRANTY

## MOBILE HEATING WRAP - SCHUKO

| DESCRIPTION | POWER @10 °C | CURRENT |
|---|---|---|
| Mobile heating wrap 5 m, Schuko plug | 75 W | 0.3 A |
| Mobile heating wrap 10 m, Schuko plug | 150 W | 0.7 A |
| Mobile heating wrap 15 m, Schuko plug | 225 W | 1.0 A |
| Mobile heating wrap 20 m, Schuko plug | 300 W | 1.3 A |
| Mobile heating wrap 25 m, Schuko plug | 375 W | 1,6 A |

## MOBILE HEATING WRAP - IEC309

| DESCRIPTION | POWER @10 °C | CURRENT |
|---|---|---|
| Mobile heating wrap 5 m, IEC309 plug | 75 W | 0.3 A |
| Mobile heating wrap 10 m, IEC309 plug | 150 W | 0.7 A |
| Mobile heating wrap 15 m, IEC309 plug | 225 W | 1.0 A |
| Mobile heating wrap 20 m, IEC309 plug | 300 W | 1.3 A |
| Mobile heating wrap 25 m, IEC309 plug | 375 W | 1,6 A |

## MOBILE HEATING WRAP - DK

| DESCRIPTION | POWER @10 °C | CURRENT |
|---|---|---|
| Mobile heating wrap 5 m, DK plug | 75 W | 0.3 A |
| Mobile heating wrap 10 m, DK plug | 150 W | 0.7 A |
| Mobile heating wrap 15 m, DK plug | 225 W | 1.0 A |
| Mobile heating wrap 20 m, DK plug | 300 W | 1.3 A |
| Mobile heating wrap 25 m, DK plug | 375 W | 1,6 A |

Version 2-102023

Heatcom Corporation A/S
Barmstedt Allé 6
5500 Middelfart
Tel. +45 63 41 77 77
Sales@Heatcom.dk